

# ***SUCTION HOSE***

## **9903 / 9906 – RUBBER VAC HOSE**

### **9903 ASSEMBLIES WITH MALE & FEMALE CAM LOCK COUPLINGS**



2" X 20'	9903-2X20CE
2-1/2" X 20'	9903-250X20CE
3" X 20'	9903-3X20CE
4" X 20'	9903-4X20CE
6" X 20'	9903-6X20CE

CORRUGATED COVER - SMOOTH STATIC DISSIPATING TUBE

A LIGHT DUTY DUCT HOSE VERSION IS ALSO AVAILABLE (FULL ROLLS ONLY)

### **9906 ASSEMBLIES WITH MALE & FEMALE CAM LOCK COUPLINGS**



2" X 20'	9906-2X20CE
2-1/2" X 20'	9906-250X20CE
3" X 20'	9906-3X20CE
4" X 20'	9906-4X20CE
6" X 20'	9906-6X20CE

SMOOTH COVER - SMOOTH STATIC DISSIPATING TUBE

FLEXIBLE IN COLD WEATHER – DURABLE AND ABRASION RESISTANT DESIGN

**TYPE 9903 AND 9906 HAVE A PVC HELICAL REINFORCEMENT EMBEDDED WITHIN THE WALL**

*USE WIRE REINFORCED HOSE IN HIGH HEAT APPLICATIONS*

**-30 TO + 140 DEG F**

### **BULK HOSE**

**-30 TO + 140 DEG F**

#### **9903 CORRUGATED COVER**

#### **9906 SMOOTH COVER**

SIZE ID:	ITEM NUMBER	PSI RATING	LBS / FT
1-1/2"	9903-150	50	0.40
2"	9903-200	40	0.55
2-1/2"	9903-250	35	0.78
3"	9903-300	35	1.05
4"	9903-400	30	1.68
6"	9903-600	25	3.20
8"	9903-800	25	5.75

SIZE ID:	ITEM NUMBER	PSI RATING	LBS / FT
1-1/2"	9906-150	70	0.60
2"	9906-200	60	0.80
2-1/2"	9906-250	45	1.10
3"	9906-300	45	1.45
4"	9906-400	45	2.30
6"	9906-600	30	4.00

*FULL VACUUM RATING IN ALL SIZES (AT AMBIENT TEMPERATURE)*

**PSI RATING LISTED IS THE RECOMMENDED MAX OPERATING PRESSURE OF THE BULK HOSE ONLY  
HOSE ASSEMBLY WORKING PRESSURE RATING IS DEPENDENT ON THE COUPLING TYPE**