

SUCTION HOSE

7901 – STANDARD PVC SUCTION

ASSEMBLIES WITH MALE & FEMALE NPSH THREADED COUPLINGS



1-1/2" X 20'	7901-150X20MF
2" X 20'	7901-2X20MF
2-1/2" X 20'	7901-250X20MF
3" X 20'	7901-3X20MF
4" X 20'	7901-4X20MF
6" X 20'	7901-6X20MF

ASSEMBLIES WITH MALE & FEMALE CAM LOCK COUPLINGS



1-1/2" X 20'	7901-150X20CE
2" X 20'	7901-2X20CE
2-1/2" X 20'	7901-250X20CE
3" X 20'	7901-3X20CE
4" X 20'	7901-4X20CE
6" X 20'	7901-6X20CE

CORRUGATED COVER AVAILABLE

FOR ASSEMBLIES WITH FEMALE CAM X MALE NPT:
REPLACE THE CE IN ABOVE PART NUMBER WITH CN

8" – 12" ASSEMBLIES AVAILABLE WITH CAM, FLANGE, NPT OR BALL & SOCKET COUPLINGS

100 FT MAX ROLL THROUGH 6"

BULK HOSE

-10 TO +130 DEG F

SIZE (ID)	ITEM NUMBER	PSI RATING	LBS / FOOT
1"	7901-100	90	0.28
1-1/4"	7901-125	90	0.36
1-1/2"	7901-150	90	0.48
2"	7901-200	70	0.67
2-1/2"	7901-250	65	0.94
3"	7901-300	55	1.20

SIZE (ID)	ITEM NUMBER	PSI RATING	LBS / FOOT
4"	7901-400	50	1.90
5"	7901-500	45	3.05
6"	7901-600	45	4.60
8"	7901-800	40	7.10
10"	7901-10	40	12.50
12"	7901-12	35	15.75

CAPABLE OF FULL VACUUM THROUGH 8 INCH DIAMETER (AT AMBIENT TEMPERATURE)

FOR INCREASED FLEXIBILITY SEE TYPE 7909 LOW TEMP CLEAR PVC SUCTION HOSE

**PSI RATING LISTED IS THE RECOMMENDED MAX OPERATING PRESSURE OF THE BULK HOSE ONLY
HOSE ASSEMBLY WORKING PRESSURE RATING IS DEPENDENT ON THE COUPLING TYPE**